

Wall mounted unit

FTX-KM



Energy saving during standby mode



Vertical auto swing



Auto fan speed



Dry programme



Titanium apatite photocatalytic air purification filter

Discreet wall mounted unit providing high efficiency and comfort

- › Discreet, stylish front panel blends easily with the wall, and matches all interior décors
- › Dry programme allows humidity levels to be reduced without variations in room temperature
- › Daikin outdoor units are neat, sturdy and can easily be mounted on a roof or terrace or simply placed against an outside wall
- › Outdoor units are fitted with a swing compressor, renowned for its low noise and high energy efficiency
- › Outdoor units for pair application

FTX-KM + RX-KM




Indoor unit		FTX	25KM	35KM
Casing	Colour		White	
Dimensions	Unit	HeightxWidthxDepth	mm	
			285x770x225	
Sound power level	Cooling		dBA	
			55	
Sound pressure level	Heating		dBA	
			55	56
Control systems	Cooling	High/Low/Silent operation	dBA	
			40/26/20	43/27/20
	Heating	High/Low/Silent operation	dBA	
			40/28/25	43/29/26
	Infrared remote control		ARC470A1	
	Wired remote control		BRC944B2 / BRC073A1	

Efficiency data		FTX + RX	25KM + 25KM	35KM + 35KM
Cooling capacity	Nom.	kW	2.5	3.5
Heating capacity	Nom.	kW	2.8	3.3
Power input	Cooling	Nom.	kW	
			0.706	1.028
Seasonal efficiency (according to EN14825)	Heating	Nom.	kW	
			0.698	0.943
Energy label	Cooling	Energy label	A+	
		Pdesign	kW	
			2.50	3.30
		SEER		
			5.93	6.02
		Annual energy consumption	kWh	
Energy label	Heating (Average climate)	Energy label	A+	
		Pdesign	kW	
			2.40	2.80
		SCOP/A		
			4.01	4.04
		Annual energy consumption	kWh	
Nominal efficiency	EER		3.54	
	COP		4.01	
	Annual energy consumption		kWh	
			353	514
Energy label	Cooling/Heating		A/A	

Outdoor unit		RX	25KM	35KM
Dimensions	Unit	HeightxWidthxDepth	mm	
			550x675x284	
Sound power level	Cooling		dBA	
			60	62
Sound pressure level	Heating		dBA	
			61	63
Operation range	Cooling	High	dBA	
			46	48
Refrigerant	Heating	High	dBA	
			47	48
Power supply	Cooling	Ambient	Min.~Max. °CDB	
			10 ~46	
	Heating	Ambient	Min.~Max. °CWB	
			-15~18	
Refrigerant	Type/Charge/GWP	kg/CO ₂ eq	R-410A/0.70/1.5/2,087.5	R-410A/0.94/2.1/2,087.5
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240	

Operation range in combination with FTX-J3: min. 10°CDB ~ max. 46°CDB | Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN16-042 07/16



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.